



K33 is a 3-point truss specially designed for small to medium sized structures on stage. They are very popular models stocked by many companies that are in hire and productions business and they are also widely used for permanent installation.

It comes in different lengths at 0.5m, 1.0m, 1.5m, 2.0m, 2.5m, and 3.0m. K33 features 50mm outer diameter with 2mm wall thickness.

All KKMark trusses are made of T6 6082 aluminium sourced from Taiwan.

Material	T6 6082 (Taiwan)
Main Tube	50mm
Diagonal Bracing	20mm
Wall Thickness	2mm



Length	Uniform Distributed Load	Deflection	Center Point Load	Deflection	Two Point Load	Deflection	Three Point Load	Deflection
Meters	Kg	cm	Kg	cm	Kg	cm	Kg	cm
1	1,901.0	-	779.5	-	710.0	-	599.4	-
2	867.0	0.3	598.4	0.4	518.4	0.5	409.2	0.3
3	384.2	0.7	485.6	0.6	408.9	0.7	287.0	0.6
4	215.2	1.2	408.5	0.9	320.4	1.1	213.5	1.2
5	134.1	1.8	337.5	1.6	253.1	1.8	168.5	1.7
6	92.5	2.5	279.4	2.0	208.4	2.7	139.0	2.6
7	66.7	3.7	235.8	2.9	175.6	3.8	116.2	3.4
8	49.5	4.5	200.7	3.8	151.4	4.7	101.4	4.5
9	38.1	5.9	175.8	4.7	132.5	6.1	87.5	5.5
10	31.2	7.4	152.9	5.6	116.0	7.4	67.5	7.0
11	24.5	8.6	134.8	7.2	101.5	8.9	54.2	8.5
12	19.7	10.6	118.9	8.4	90.7	10.7	48.6	10.0